



## MODEL DS – RIGID FRAME DOCK SHELTER

### FEATURE SUMMARY

- High-Tear Abrasion Resistant Fabrics With Double Lock Stitched Seams
- Kiln Dried Pressure Treated Superior Grade Side & Head Frame Lumber With Translucent Covers to Allow in Natural Light
- Head & Side Curtains Inserted With Stays & Foam Bead on Inside Edge to Conform & Retain a Tight Seal Against Trailer Top & Sides
- Head Curtain Provided With Overlapping Wear Pleats in Corners & Retention Cords
- Wear Caps on Bottom Corners of Face Curtains Provides Additional Wear Strength
- Guide Stripes Help Accurate Truck Positioning
- Bottom Corner Draft Pads With “No Step” Imprint
- Heavy-Duty Steel Guards Support Side Frame & Provide Protection From Incoming Trailers
- Most Suitable for Door Openings Up To 10 Feet Wide x 10 Feet High
- Galvanized Mounting Hardware Included



### DESCRIPTION

The WEARTOUGH® Series of full access dock shelters provide effective protection for personnel and cargo while loading and off loading trailers. The truck backs into the side and top curtains to help keep out inclement weather, dust and insects creating a more productive and safer environment while saving energy costs and increasing security.

### SPECIFICATION

Dock shelter(s) to be Model DS as manufactured by Nordock Inc. to suit door size of \_\_\_\_\_ wide x \_\_\_\_\_ high and dock height of \_\_\_\_\_ with a projection of \_\_\_\_\_ to provide 12”-18” projection beyond front face of dock bumpers. Each unit shall consist of two side frames with front curtains and one head frame with head curtain. Side frames to be constructed with kiln dried pressure treated superior grade lumber and covered with translucent fiberglass. Two steel guards to be mounted beneath and project in front of side frames to provide support and protection. The side and top curtain fabric shall be \_\_\_\_\_ with sewn in stays to keep curtains tight against the truck or trailer. Head curtain drop shall be 36” long or \_\_\_\_\_ to provide a minimum 6” overlap with the lowest truck or trailer to be serviced. The head curtain shall be equal to the overall unit width and have corner wear pleats and wind retention cords. Optional Tough-Split™ gussets provide relief from tearing by corner of trailers \_\_\_\_\_. The unit shall include 24” high \_\_\_\_\_ or optional full height \_\_\_\_\_ yellow guide stripes to aid in trailer positioning.

### WARRANTY

Nordock guarantees that the DS Model of dock shelters will perform as described and to the full satisfaction of the purchaser for one-year from date of receipt. Consult your Nordock representative for assistance in choosing the correct size and options for your application.

### FABRIC OPTIONS:


- 22 oz. Vinyl
- 40 oz. Vinyl
- 50oz. WT-90 WEARTOUGH®

### ADDITIONAL OPTIONS:

- Dock Levelers
- Vehicle Restraints
- Loading Dock Lights

### SHELTER OPTIONS:

- TOUGH-SPLIT™ Head Curtain Gussets
- TERMINATOR™ Trailer Door Gap Seal
- Tapered Sides for Decline/Incline Approach
- Spray & Hot Dip Galvanized Steel Frames
- White Vinyl or Steel Covers in Lieu of Fiberglass



TERMINATOR™



TOUGH-SPLIT™

\* Nordock Inc. reserves the right to make changes to specifications without notice or obligation.