

MODEL STP – TRAILER DOOR GAP COMPRESSION SEAL



FEATURE SUMMARY

- **Unique Side Pad Design Captures & Closes Off The Air Gap Created by Swing Out Trailer Doors**
- **High-Tear Abrasion Resistant Fabrics With Double Lock Stitched Seams**
- **Kiln Dried Pressure Treated Superior Grade Backing & Head Frame Lumber**
- **99 % Memory Foam Core Side Frame With Condensation Drainage System**
- **Fixed Head Pad Provides Maximum Seal**
- **Full Height Yellow Guide Stripes on Inside Face & Bright Orange on Outside Face of Vertical Pads for Accurate Truck Positioning**
- **Better Trailer Access With Less Pressure on Building Wall Then Conventional Foam Pad Seals**
- **Most Suitable for Door Openings Up To 9 Feet Wide x Up To 9 Feet High**
- **Galvanized Mounting Hardware Included**

DESCRIPTION

The WEARTOUGH® Series dock seal is designed to form a tight seal against the trailer doors to provide effective protection for personnel and cargo while loading and off loading trailers. The truck backs into the side pads and head pad to keep out inclement weather, dust and insects creating a more productive and safer environment while saving energy costs and increasing security. The unique design closes the gap created from swing out trailer doors, lessens the pressure on building walls and allows a clearer access into the trailer.

SPECIFICATON

Dock seal(s) to be Model STP as manufactured by Nordock Inc. to suit door size of _____ wide x _____ high and dock height of _____ with a projection of _____ to suit _____ of dock bumper projection. Each unit shall consist of two fabric covered foam side pads and one head pad. Side pads to be constructed with 99% compression recovery polyurethane foam core continuously bonded to pressure treated superior backing lumber and fully wrapped with the base fabric. The base fabric shall be _____. The side vertical side pads to be shaped to accommodate trailer widths of 8 feet to 8' 6" in width with a second layer of high-visibility orange on outside face and a full height yellow guide stripe on inside to aid in driver positioning. Taper side pads if needed to suit an approach grade percentage of _____. Head pad height shall be _____ to provide a minimum 6" overlap with the lowest trailer/truck to be serviced. The head pad shall be equal to the overall unit width.

WARRANTY

Nordock guarantees that the STP Model of dock seals will perform as described and to the full satisfaction of the purchaser for one-year from date of receipt. Consult your Nordock representative for assistance in choosing the correct size and options for your application.

FABRIC OPTIONS:

22 oz. & 40 oz. Vinyl
40 oz. Hypalon
50oz. WT 90 WEARTOUGH®

ADDITIONAL EQUIPMENT OPTIONS:

Dock Levelers
Vehicle Restraints
Loading Dock Lights

SEAL OPTIONS:

Tapered Sides for Decline/Incline Approach
Galvanized Steel Backer
4" or 8" Exposure Wear Pleats



* Nordock Inc. reserves the right to make changes to specifications without notice or obligation.