

SERIES FFI-750



FEATURE SUMMARY

- Improves Safety & Productivity While Reducing Costs by Providing Protection From Inclement Weather, Dirt & Insects While Saving Energy
- High-Tear Abrasion Resistant Vinyl Header Bag Fabric With Double Lock Stitching
- Unique Retraction System Quickly Deflates & Returns Unit to Stored Position
- On/Off Switch With Pilot Light
- Galvanized Mounting Hardware
- Motor/Blower Mounted in Header
- Kiln Dried Pressure Treated Superior Grade Backing & Head Frame Lumber
- 99 % Memory Foam Core Side Frame Prevents Damage From Off Center Trailers
- Side Curtains Inserted With Stays & Foam Bead on Inside Edge to Conform & Retain a Tight Seal Against Trailer Sides
- 24" High Yellow Guide Stripes on Bottom of Pads for Accurate Truck Positioning
- Bottom Corner Draft Pads
- Most Suitable for Door Openings Up To 10 Feet Wide x 10 Feet High

DESCRIPTION

The FFI-750 Series of foam side inflatable header dock shelters provide the ultimate protection for personnel and cargo while loading and off loading trailers. The inflated head seal pushes tight against the top of the trailer and the vertical curtains push on the sides of the trailer to help keep out inclement weather, dust and insects creating a more productive and safer environment while saving energy costs and increasing security.

OPERATION

Once the trailer is positioned against the bumpers for loading, the operator switches the control button to start the blower that in turn inflates the header bag assembly creating a tight seal while allowing clear access into the trailer. The blower runs continuous as long as the loading or off loading is being carried out. When loading is complete, the operator turns off the switch and the header bag automatically retracts away from the trailer.

CONSTRUCTION

The header bag is constructed from flexible and UV resistant High-Tear vinyl fabric, double lock stitched and attached to the pressure treated lumber or optional steel framing. The 1/2 HP 115 volt or optional 230 volt motor/blower is integral mounted within the head frame. The on/off switch is mounted to the interior wall and equipped with a power on pilot light. A torsion spring retraction system is mounted within the head frame. Each unit shall consist of (2) two fabric covered foam side pads constructed with 99% compression recovery polyurethane foam core continuously bonded to pressure treated superior backing lumber and fully wrapped with the base fabric. The front side curtains to have sewn in stays to keep a tight seal against the sides of the trailer and yellow guide stripes to aid in positioning. Corner bottom pads seal the bottom side sections. All mounting hardware is galvanized steel.

SIDE CURTAIN FABRIC OPTIONS:

22 oz. & 40 oz. Vinyl
40 oz. Hypalon
50oz. WT-90 WEARTOUGH®

SHELTER OPTIONS:

Terminator™ Trailer Door Seal
Full Height Yellow Guide Stripes
Tapered Sides for Decline/Incline Approach
Steel Head Frame or Backer

ADDITIONAL EQUIPMENT OPTIONS:

Dock Levelers
Vehicle Restraints
Loading Dock Lights



* Nordock Inc. reserves the right to make changes to specifications without notice or obligation.

NORDOCK® INC.

Nordock products are covered by various U.S. and foreign patents & applications.

Website: www.nordockinc.com ~ Email: Sales@nordockinc.com ~ Toll Free: 866-885-4276