

MODEL RF – RETRACTABLE DOCK SHELTER

FEATURE SUMMARY



- High-Tear Abrasion Resistant Fabrics With Double Lock Stitched Seams
- Gravity Forward Operating System
- Rugged Steel Frame Prevents Damage From Off Center Trailers
- Head & Side Curtains Inserted With Stays & Foam Bead on Inside Edge to Conform & Retain a Tight Seal Against Trailer Top & Sides
- Head Curtain Provided With Overlapping Wear Pleats in Corners & Retention Cords
- 24" High Yellow Guide Stripes on Bottom of Pads for Accurate Truck Positioning
- Bottom Corner Draft Pads With "No Step" Imprint
- Translucent Vinyl Top & Side Covers Allow in Natural Light
- Most Suitable for Door Openings Up To 10 Feet Wide x 10 Feet High
- Galvanized Mounting Hardware Included

DESCRIPTION

The WEARTOUGH® Series of full access dock shelters provide effective protection for personnel and cargo while loading and off loading trailers. The truck backs into the side and top curtains to help keep out inclement weather, dust and insects creating a more productive and safer environment while saving energy costs and increasing security.

SPECIFICATON

Dock shelter(s) to be Model RF as manufactured by Nordock Inc. to suit door size of _____ wide x _____ high and dock height of _____ with a projection of _____ to provide 12"-18" projection beyond front face of dock bumpers. Each unit shall consist of retractable steel side and top frames covered on top and sides with white vinyl. Vertical side curtains and head curtain to be attached to steel frame with aluminum trim angle. The front side and top curtain to have sewn in stays to keep tight against the truck and fabric shall be _____. Head curtain drop shall be 36" long or _____ to provide a minimum 6" overlap with the lowest trailer/truck to be serviced. The head curtain shall be equal to the overall unit width and have corner wear pleats and wind retention cords and with optional Tough-Split™ gussets to provide relief from tearing by corner of trailers _____. The unit shall include 24" high _____ or optional full height _____ yellow guide stripes to aid in trailer positioning. Two steel protective guards and galvanized mounting hardware included.

WARRANTY

Nordock guarantees that the RF Model of dock shelters will perform as described and to the full satisfaction of the purchaser for one-year from date of receipt. Consult your Nordock representative for assistance in choosing the correct size and options for your application.

FABRIC OPTIONS:

22 oz. & 40 oz. Vinyl
40 oz. Hypalon
50oz. WT 90 WEARTOUGH®

ADDITIONAL EQUIPMENT OPTIONS:

Dock Levelers
Vehicle Restraints
Loading Dock Lights
Galvanized Steel Canopies

SHELTER OPTIONS:

Tough-Split™ Head Curtain
Full Height Yellow Guide Stripes
Tapered Sides for Decline/Incline Approach
Galvanized Steel Frame



* Nordock Inc. reserves the right to make changes to specifications without notice or obligation.

NORDOCK® INC.

Nordock products are covered by various U.S. and foreign patents & applications.

Website: www.nordockinc.com ~ Email: Sales@nordockinc.com ~ Toll Free: 866-885-4276