

MODEL FP – FIXED HEAD PAD DOCK SEAL



FEATURE SUMMARY

- Improves Safety & Productivity While Reducing Costs by Providing Protection From Inclement Weather, Dirt & Insects While Saving Energy
- High-Tear Abrasion Resistant Fabrics With Double Lock Stitched Seams
- Kiln Dried Superior Grade Backing Lumber
- 99 % Memory Foam Core For Extended Life
- Fixed Head Pad Provides Maximum Seal
- Condensation Drainage System
- 24" High Yellow Guide Stripes on Bottom of Pads for Accurate Truck Positioning
- Most Suitable for Door Openings Up To 9 Feet Wide x 9 Feet High
- Galvanized Mounting Hardware Included

DESCRIPTION

The WEARTOUGH™ Series of dock seals provide effective protection for personnel and cargo while loading and off loading trailers. The truck pushes tight against the side and top of the seal to help keep out inclement weather, dust and insects creating a more productive and safer environment while saving energy costs and increasing security.

SPECIFICATION

Dock door seal(s) to be Model FP as manufactured by Nordock Inc. to suit door size of _____ wide x _____ high and dock height of _____ with a projection of _____ to provide 4-6" beyond front face of dock bumpers. Each unit shall consist of (2) two side pads and one head pad. Taper side pads if needed to suit an approach grade percentage of _____. Side and head pads to be constructed with 99% compression recovery polyurethane foam core continuously bonded to kiln dried superior backing lumber and fully wrapped with the base fabric. The base fabric shall be _____. The second layer of fabric for wear pleats shall be _____ with a _____" face exposure. The second layer of fabric for wear faces shall be _____ on inside ____ / front face _____. Head pad height shall be _____ to provide 4" overlap with the highest trailer/truck to be serviced. Optional drop curtain off head pad to overlap trucks lower than door opening to be either base fabric ____ or PVC strips ____ with length of _____. The unit shall include 24" high ____ or optional full height ____ yellow guide stripes to aid in trailer positioning.

WARRANTY

Nordock guarantees that the FP Model of dock seals will perform as described and to the full satisfaction of the purchaser for one-year from date of receipt. Consult your Nordock representative for assistance in choosing the correct size and options for your application.

FABRIC OPTIONS:

22 oz. & 40 oz. Vinyl
16 oz. & 40 oz. Hypalon
50oz. WT 90 WEARTOUGH™

SEAL OPTIONS:

4", 6" & 8" Exposure Wear Pleats
Fabric or PVC Strip Header Drop Curtain
Full Height Yellow Guide Stripes
Extra Layer of Fabric on Front or Inside Face

ADDITIONAL EQUIPMENT OPTIONS:

Galvanized Steel Canopies
Loading Dock Lights



* Nordock Inc. reserves the right to make changes to specifications without notice or obligation.

NORDOCK INC.

Nordock products are covered by various U.S. and foreign patents & applications.

Website: www.nordockinc.com ~ Email: Sales@nordockinc.com ~ Toll Free: 866-885-4276