

MODEL FC – CURTAIN STYLE DOCK SEAL



FEATURE SUMMARY

- Improves Safety & Productivity While Reducing Costs by Providing Protection From Inclement Weather, Dirt & Insects While Saving Energy
- High-Tear Abrasion Resistant Fabrics With Double Lock Stitched Seams
- Kiln Dried Pressure Treated Superior Grade Backing Lumber
- 99 % Memory Foam Core For Extended Life
- Head Curtain With Velcro Splits and Wrap Around End Caps
- Condensation Drainage System
- Full Height Yellow Guide Stripes on Vertical Pads for Accurate Truck Positioning
- Most Suitable for Door Openings Up To 9 Feet Wide x 10 Feet High
- Galvanized Mounting Hardware Included

DESCRIPTION

The WEARTOUGH® Series of dock seals provide effective protection for personnel and cargo while loading and off loading trailers. The truck pushes tight against the side and top of the seal to help keep out inclement weather, dust and insects creating a more productive and safer environment while saving energy costs and increasing security.

SPECIFICATION

Dock door seal(s) to be Model FC as manufactured by Nordock Inc. to suit door size of _____ wide x _____ high and dock height of _____ with a projection of _____ to provide 4-6" projection beyond front face of dock bumpers. Each unit shall consist of (2) two side pads and one head curtain. Taper side pads if needed to suit an approach grade percentage of _____. Side pads to be constructed with 99% compression recovery fire retardant polyurethane foam core continuously bonded to kiln dried pressure treated superior backing lumber and fully wrapped with the base fabric. The base fabric shall be _____. The second layer of fabric for wear pleats shall be _____ with a _____" face exposure. The second layer of fabric for wear faces shall be _____ on inside ____ / front face _____. Head curtain drop shall be 18" long or _____ to provide 6" overlap with the lowest trailer/truck to be serviced. The curtain shall be equal to the overall unit width and be either fixed ____ or adjustable ____ with velcro splits. The unit shall include full height yellow guide stripes to aid in trailer positioning.

WARRANTY

Nordock guarantees that the FC Model of dock seals will perform as described and to the full satisfaction of the purchaser for one-year from date of receipt. Consult your Nordock representative for assistance in choosing the correct size and options for your application.

FABRIC OPTIONS:

22 oz. & 40 oz. Vinyl
40 oz. Hypalon
50oz. WT 90 WEARTOUGH®

SEAL OPTIONS:

4" or 8" Exposure Wear Pleats
Adjustable Head Curtain
Half or Full Foam Filled Curtain
Extra Layer of Fabric on Front or Inside Face

ADDITIONAL EQUIPMENT OPTIONS:

Dock Levelers
Vehicle Restraints
Galvanized Steel Canopies
Loading Dock Lights



* Nordock Inc. reserves the right to make changes to specifications without notice or obligation.

NORDOCK® INC.

Nordock products are covered by various U.S. and foreign patents & applications.

Website: www.nordockinc.com ~ Email: Sales@nordockinc.com ~ Toll Free: 866-885-4276