



MODEL	PIT DIMENSIONS						
	DIM "A"	DIM "B"	DIM "C"	DIM "D"	DIM "E"	DIM "F"	DIM "G"
6 x 5	51"	12"	12-1/2"	83-1/2"	72"	74"	77-1/2"
6 x 6	63"	12"	12-1/2"	83-1/2"	72"	74"	77-1/2"
6 x 8	87"	12" (15" *)	12-1/2" (15-1/2" *)	83-1/2"	72"	74"	77-1/2"
6.5 x 5	51"	12"	12-1/2"	89-1/2"	78"	80"	83-1/2"
6.5 x 6	63"	12"	12-1/2"	89-1/2"	78"	80"	83-1/2"
6.5 x 8	87"	12" (15" *)	12-1/2" (15-1/2" *)	89-1/2"	78"	80"	83-1/2"
7 x 5	51"	12"	12-1/2"	95-1/2"	83"	85"	89-1/2"
7 x 6	63"	12"	12-1/2"	95-1/2"	83"	85"	89-1/2"
7 x 8	87"	12" (15" *)	12-1/2" (15-1/2" *)	95-1/2"	83"	85"	89-1/2"

\* OPTION FOR DEEPER PIT TO INCREASE BELOW DOCK SERVICE RANGE

- RECOMMENDED BUMPER HEIGHT: 50"
- RECOMMENDED DOCK HEIGHT: 50"
- RECOMMENDED DOOR OPENING HEIGHT: 10'0"

#### NOTES:

- ALL MATERIALS (CONCRETE, STEEL, CONDUITS, ETC.), UNLESS OTHERWISE SPECIFIED, ARE TO BE SUPPLIED AND INSTALLED BY OTHERS
- REAR EMBED ASSEMBLY TO BE PLUMB WITHIN 1/16"
- REAR EMBED TO BE PARALLEL TO FRONT CURB ANGLE WITHIN 1/8"
- Ø OF REAR EMBED AND Ø OF DOOR JAMB TO BE WITHIN 1/8"

I.D.	QTY.	PART NO.	DESCRIPTION	MAT'L	WGT.
<b>NORDOCK</b>					
PIT DETAIL & SURVEY SHEET NV, ENCLOSED PIT					
DO NOT SCALE DRAWING - UNLESS OTHERWISE SPECIFIED DIM ARE IN INCHES ANGULAR TOL. ±0°30'    FRAC. TOL. ±1/32"    DEC. TOL. ±0.10					
DATE:	05/02/10	DR:	DH	APP'D:	SCALE:
SHEET #	1 OF 1	DWG. NO.:	49-0096	REV:	DNS

THE INFORMATION HEREON IS THE PROPERTY OF NORDOCK INC. BY ACCEPTING THIS INFORMATION THE BORROWER AGREES THAT IT WILL NOT BE USED FOR ANY PURPOSE OTHER THAN THAT FOR WHICH IT WAS PROVIDED.