

NORDOCK LOADING DOCK EQUIPMENT

Model (EM) Edge of Dock Leveler Architectural Specifications

A. Manufacturer

1. Design is based on products manufactured by;
Nordock Inc.
740 Beechcroft Rd.
Spring Hill, TN 37174
800-251-3382
(931) 486-2296
2. Type: Loading dock leveler shall be fully mechanical Bar type activation with torsion spring lift assist.

B. Product Characteristics: Dock Levelers

1. Product: Fully mechanical Edge of Dock leveler – Model EM ____
2. Size: ____” wide with an overall span (dock to truck bed) of 27 $\frac{3}{4}$ ”.
3. Capacity: 20,000 lbs., 30,000 lbs., & 40,000 lbs. capacities available.
4. Construction: Center plate and lip plate, 55,000 lb. minimum yield steel tread plate. Lip hinge pin shall be totally enclosed supported by hinge tubes with grease fittings. The lip hinge tubes shall be supported by a full width distribution bar.
5. Operation: Conveniently located Cantilever Style recessed handle provides easy activation of center plate and lip. Lip to automatically extend and engage truck bed when Bar is pushed forward.
6. Lift Assist: Provided Torsion Spring with bar lift allows operation of unit using no more than 28 – 34 lbs. Provide single point adjustment capability. Levelers and warranty shall meet or exceed the performance requirements of CS202-56, O.S.H.A. and ANSI MH-14.1. 1 – 1984.
7. Bumpers: Two per dock leveler.