MODEL EM
EDGE MOUNT
MECHANICAL DOCK LEVELER

NORDOCK®
DEDICATED PEOPLE ~ SUPERIOR PRODUCTS


The Model EM Edge-of-Dock Leveler delivers rugged, reliable dock-to-truck access with a simple, spring-assisted design. It ensures fast installation, smooth operation, and durable performance at a competitive price.



AFFORDABLE. DURABLE. RELIABLE.


- **20,000 - 40,000 LB. CAPACITIES**
- **66", 72", 78" & 84" WIDTHS**
- **FAST INSTALLATION**
- **HEAVY-DUTY DOCK BUMPERS**
- **NO PIT NECESSARY**

FEATURES & BENEFITS




HEAVY DUTY STEEL CONSTRUCTION

55,000 PSI minimum yield steel tread plate for exceptional strength & durability.



MECHANICAL SPRING LIFT ASSIST

Counterbalanced Torsion spring lift assist reduces operator effort and improves safety.




CONTINUOUS PIANO HINGE DESIGN

Continuous rear hinge with grease fittings included for extended service life.


COST EFFECTIVE ALTERNATIVE

Few moving parts, easy adjustment & minimal maintenance requirements.



RUGGED STRUCTURAL DESIGN

Three formed steel gussets provide up to 30,000 Lbs. of structural support while stored.



EASY BAR-LIFT OPERATION

Single Pull-and-Lift operating handle. Fast one person operation without hydraulic power.

IDEAL FOR | DISTRIBUTION CENTERS | MANUFACTURING FACILITIES | WAREHOUSES | MUNICIPAL OPERATIONS | COMMERCIAL LOADING DOCKS

WWW.NORDOCKINC.COM | SALES@NORDOCKINC.COM | TOLL FREE: 1-866-885-4276

MODEL EM
MECHANICAL EDGE OF DOCK LEVELER

SPECIFICATIONS

DESCRIPTION

The NORDOCK® Model EM Mechanical Edge-of-Dock Leveler provides dependable, economical loading dock service for a wide variety of applications. Available in multiple widths & capacities, the Model EM combines rugged construction, simple operation, & long-lasting performance.

Constructed with a 55,000 PSI minimum yield steel tread plate deck & lip, the Model EM is designed to withstand demanding loading dock environments while providing reliable service year after year.


The torsion spring lift assist system minimizes operator effort while allowing smooth deployment onto the truck bed.

AVAILABLE CAPACITIES (LBS.)
20K | 30K | 40K


STANDARD WIDTHS
66" | 72" | 78" | 84"

OPERATION

1. The operator lifts the bar lift handle from it's stored position & pull it back until the deck reaches its fully raised position.



2. The handle is then pushed forward, extending the lip onto the truck bed.



3. The deck automatically returns to its stored position after truck departure.



The EM Model requires no pulling or straining, allowing comfortable one-person operation.

CONSTRUCTION

- 55,000 PSI minimum yield steel tread plate
- Three formed steel gussets provide structural support while stored
- Continuous rear hinge with grease fittings
- Mechanical torsion spring lift assist
- Molded rubber dock bumpers
- Formed steel bumper blocks
- Heavy-duty center plate and lip construction
- Durable welded steel frame

BUILT TO PERFORM. BUILT TO LAST.
The Model EM is engineered to stand the toughest loading dock environments.

SUBMITTAL INFORMATION

PROJECT INFORMATION

Job Name: _____

Address: _____

General Contractor: _____

Distributor: _____

Model: _____

Quantity: _____

Capacity: ☐20K ☐30K ☐40K

Integrated Control: ☐Yes ☐No

CERTIFIED FOR CONSTRUCTION

Date: _____

Company: _____

Address: _____

Notes:

MODELS & NOMINAL DIMENSIONS

MODEL*	WIDTH	OVERALL WIDTH
EM-66	66"	104"
EM-72	72"	110"
EM-78	78"	116"
EM-84	84"	122"


***Add capacity to model number.**
Example: EM-72-30.

Contact a sales representative at 1-866-885-4276 or email sales@nordockinc.com for more information.

OPTIONS & ACCESSORIES


VEHICLE RESTRAINTS


RESTRAINT CONTROL PANEL


DOCK SEALS & SHELTERS


SAFETY BARRIER GATES


WEATHER SEAL SYSTEMS


DOCK & SIGNAL LIGHTS

WARRANTIES





NORDOCK® Inc. reserves the right to make changes to specifications without notice or obligation. NORDOCK® products are covered by numerous U.S. and foreign patents and pending applications.